

Technical Data Sheet



WATER REPEL(S)

Page 1/3

**Clear Waterproofer & Protector
Vapour- Permeable Ideal for
Brick, Wood and Concrete**



Water Repel is ready-to-use, solvent-based, masonry water-repellent. It is ideal for use on standard building materials like brickwork, concrete and wood, and will also help to prevent water damage to stonework, leather, canvas, etc. Water Repel penetrates readily into most porous surfaces to form a clear, hydrophobic layer in the substrate's pore structure, thus preventing the ingress of moisture.

Larsen Building Products (I) Pvt. Ltd.

Tiles & Stone Adhesive | Grouting | Screeds | Waterproofing | Admixture | Epoxy Flooring

Rajasthan Office : 208, Ganpati Tower, Amrapali Marg, Vaishali Nagar, Jaipur-302 021-Rajasthan
Head Office : A-1, TST Mansion, Tsimshatsuei Kowloon Hong Kong
E-mail : support@neolarsen.com, www.neolarsen.com • C. Care : +91-9982388929

Water Repel (S)

PRODUCT INFORMATION	
Form :	Liquid
Standard Colour (s) :	Clear
Flash Point :	.-38°C
Hazard Information :	FLAMMABLE / HARMFUL – Consult Safety Datasheet before use
Cleaning :	Clean tools, equipment, etc. using thinners or appropriate solvents. Mechanical means are necessary when the product has set.
Packaging:	1 Ltr., 5Ltr. And 20 Ltr.
Storage Conditions :	Store in sealed containers in dry conditions, protected from extremes of temperature.
Shelf Life :	12 months in unopened manufacturer's packing
APPLICATION INFORMATION	
Application Temperature:	+.3°C to 30°C
Coverage :	Dependent on nature of substrate. Approx. 3 – 8 m ² / L
Typical Life Expectancy :	7 – 10 years

Larsen Building Products (I) Pvt. Ltd.

Tiles & Stone Adhesive | Grouting | Screeds | Waterproofing | Admixture | Epoxy Flooring

Rajasthan Office : 208, Ganpati Tower, Amrapali Marg, Vaishali Nagar, Jaipur-302 021-Rajasthan
Head Office : A-1, TST Mansion, Tsimshatsuei Kowloon Hong Kong
E-mail : support@neolarsen.com, www.neolarsen.com • C. Care : +91-9982388929

DIRECTION FOR USE



Page 3/3

WATER REPEL (S)

PREPARATION

Ensure all substrates are clean and free from contamination. Substrates must be completely dry. It is recommended to allow 2 full drying days before application. Always treat a trial area first as surface treatments may sometimes highlight existing defects, e.g. efflorescence. Ensure all mortar and pointing is in good condition. Cover windows and surroundings area to avoid splashes.

DIRECTIONS

Ensure by surface is prepared as detailed above. Water Repel is supplied ready for use and should not be further diluted. Apply by brush or low pressure spray. Apply at least two coats liberally to the surface. More porous substrates will require further application. Allow 4 hours between coats.

RESTRICTIONS

Application to a damp surface will cause the formation of a white deposit. Dilution or contamination of the products with water will cause a white gel to be deposited – Do not use if this is the case. Water repel is Flammable – consult safety datasheet before use. All work should be carried out to current best practice and industry standards. Due to high level of water repellence provided by Water Repel, Water - based paints are not suitable for over – painting treated surfaces. Treated surfaces may be over – painted with oil – based paints. Remove all splashes on windows, etc. as soon as possible. If necessary, soften splashes with a proprietary car windscreen wash and apply vigorous rubbing with a cloth, etc.

Larsen Building Products (I) Pvt. Ltd.

Tiles & Stone Adhesive | Grouting | Screeds | Waterproofing | Admixture | Epoxy Flooring

Rajasthan Office : 208, Ganpati Tower, Amrapali Marg, Vaishali Nagar, Jaipur-302 021-Rajasthan

Head Office : A-1, TST Mansion, Tsimshatsuei Kowloon Hong Kong

E-mail : support@neolarsen.com, www.neolarsen.com • C. Care : +91-9982388929