

Technical Data Sheet



WATER REPEL(w)

Page 1/4

**ONE COAT APPLICATION GREATLY
REDUCES RAIN PENETRATION PROTECTS
AGAINST FREEZE/THAW DAMAGE
EXCELLENT PENETRATION VAPOUR
PERMEABLE
IMPROVES ENERGY PERFORMANCE**



Water Repel is a creamy silane/siloxane based impregnating water repellent. Its unique thixotropic nature allows sufficient active material to be applied in one coat, by brush roller or airless spray, even overhead.

Water Repel has been designed to penetrate deeply into silicate based mineral substrates like brick, mortar and roofing tiles to give maximum reduction in water absorption and protection from water, pollutants and freeze/thaw damage. By keeping masonry dry, the thermal performance of the wall is improved.

Water repel has a high penetration depth and creates a low water uptake in the substrate with good 'beading'. Treated surfaces remain breathable and can be over- painted.

Larsen Building Products (I) Pvt. Ltd.

Tiles & Stone Adhesive | Grouting | Screeds | Waterproofing | Admixture | Epoxy Flooring

Rajasthan Office : 208, Ganpati Tower, Amrapali Marg, Vaishali Nagar, Jaipur-302 021-Rajasthan
Head Office : A-1, TST Mansion, Tsimshatsuei Kowloon Hong Kong
E-mail : support@neolarsen.com, www.neolarsen.com • C. Care : +91-9982388929

Water Repel

PRODUCT INFORMATION	
Form :	Cream (Semi liquid)
Standard Colour (s) :	White (dries clear)
Flash Point :	75°C
Hazard Information :	Not classified as Hazardous - Wear suitable mask when spraying
Cleaning :	Clean tools, equipments etc. using warm water. Mechanical means are necessary when the product has set.
Packaging:	1kg/5kg Cane
Storage Conditions :	Store in sealed containers in dry conditions, protected from extremes of temperature
Shelf Life :	18 months in unopened manufacturer's packing
APPLICATION INFORMATION	
Application Rate:	30m ² /5kg pack
Application Method:	Brush, Lambskin Roller, Airless Spray
Application Temperature:	+5°C to 35°C
Drying Time:	30minutes to several hours depending on substrate and site conditions
Density:	0.84kg/L
Expected Life:	10-20 years depending on application

Larsen Building Products (I) Pvt. Ltd.

Tiles & Stone Adhesive | Grouting | Screeds | Waterproofing | Admixture | Epoxy Flooring

Rajasthan Office : 208, Ganpati Tower, Amrapali Marg, Vaishali Nagar, Jaipur-302 021-Rajasthan
Head Office : A-1, TST Mansion, Tsimshatsuei Kowloon Hong Kong
E-mail : support@neolarsen.com, www.neolarsen.com • C. Care : +91-9982388929

DIRECTION FOR USE



Page 3/4

WATER REPEL

PREPARATION

Water Repel (w) is designed for application on to silicate based mineral substrates like brick, roofing tiles, mortar, sandstone or similar substrates.

All substrates should be dry, clean and thoroughly sound and free from oils, grease, coatings, curing membranes or any other contaminants which may interfere with penetration. Old surfaces which are contaminated with oil, paint etc should be stripped, cleaned and allowed to dry before application.

All surfaces should be uniformly dry with no damp patches. Do not apply if rain is forecast within the next 24-48 hours.

Mortar pointing should be of good quality and all existing cracks repaired before work commences.

APPLICATION

Water Repel (w) is supplied ready for use and should not be diluted.

Application may be carried out by brush, lambskin roller or, for best results, airless spray. Apply at a rate of 100-200 g/m², typically 30 m² per 5 kg pack. The exact amount depends on absorbency of the substrate. At very high application rates the product may liquefy and run.



Larsen Building Products (I) Pvt. Ltd.

Tiles & Stone Adhesive | Grouting | Screeds | Waterproofing | Admixture | Epoxy Flooring

Rajasthan Office : 208, Ganpati Tower, Amrapali Marg, Vaishali Nagar, Jaipur-302 021-Rajasthan

Head Office : A-1, TST Mansion, Tsimshatsuei Kowloon Hong Kong

E-mail : support@neolarsen.com, www.neolarsen.com • C. Care : +91-9982388929

A second coat may be applied at any time after the first has penetrated the surface, although this is rarely required.

Care should be taken when spraying to prevent over – spray landing on surrounding areas or being carried by wind. Building elements, windows, plants etc nearby should be covered with polythene sheeting during the spraying process.

RESTRICTIONS

Water repel (w) should only be applied to dry, porous surfaces and should never be applied over painted surfaces or surfaces with existing sealers. Treated surfaces must be protected from rain until dry.

Water repel (w) should not be used if the temperature is below 5°C on a thermometer or below 3°C on a rising thermometer. All surfaces to be treated must be frost free and dry.

Not suitable for contact with bitumen or some insulation materials.

While Water Repel dries colorless darkening can occasionally occur on some substrates. It is therefore always advisable to carry out a trial area first in an inconspicuous location.

Do not allow to contaminate the water course or to enter drains.

Larsen Building Products (I) Pvt. Ltd.

Tiles & Stone Adhesive | Grouting | Screeds | Waterproofing | Admixture | Epoxy Flooring

Rajasthan Office : 208, Ganpati Tower, Amrapali Marg, Vaishali Nagar, Jaipur-302 021-Rajasthan

Head Office : A-1, TST Mansion, Tsimshatsuei Kowloon Hong Kong

E-mail : support@neolarsen.com, www.neolarsen.com • C. Care : +91-9982388929